## SALTO \ HOSPITALITY

## XS4 Mini - Tubular Latches

### XS4 MINI BY SALTO | ELECTRONIC DOOR LOCKS

Stylish design is a SALTO trademark and with the XS4 Mini, we raise the bar on this already high standard thanks to its small, discreet size combined with a modern, clean LED aesthetic. The Mini's smart compactness simplifies installation. The XS4 Mini maintains the fire rating of the door as no additional drilling of the door is required.



# XS4 Mini - Tubular Latches

### Tx150 | XS4 MINI FOR TUBULAR LATCHES

The XS4 Mini for tubular latches has been designed to be used in combination with the SALTO tubular latch model. It's an deal way to convert a basic, interior door with a tubular latch into an attractive, electronically controlled door.



#### FEATURES:

- Simple installation using just two screws when installing on new or existing tubular latch door standards.
- Clear, dual colour optical signalling indicates access authorisation. Acoustic signal optional.
- High security via high resistance, hardened anti-drill protection.
- Concealed fixing screws for greater security and improved aesthetics.
- For indoor applications: quick and easy install makes it ideal for retrofits.
- Wide range of handles, configurations and door retrofit cylindrical or tubular latch cover plates, 64mm Ø to meet the installation needs.

#### **READER COLOUR:**



PM

IΔ

PP

NF

BC

#### **TECHNICAL CHARACTERISTICS:**

- Covers door thicknesses: From 32mm up to 90mm.
- Dimensions: 127mm x 58,5mm x 22,5mm.
- Reversible handle, left or right electronic lock.
- Clutch mechanism escutcheon; when unlocked handle moves freely.
- Handle rotation: 40°.
- To be used in combination with SALTO tubular latch LT2K.
- Handle compatibility: 16mm Ø.
- Square spindles available: 7,6mm split and 8mm.


#### PLATFORMS:




#### **ID TECHNOLOGIES :**

- MIFARE<sup>®</sup> (DESFire EV1, Plus, Ultralight C, Classic ISO/IEC 14443).
  Bluetooth SMART (BLE).
- NFC.

#### HANDLES:



#### **TECHNICAL DRAWING:**



#### **CERTIFICATIONS:**



### **Technical Data**

#### **POWER SOURCE:**

• XS4 Mini: 3 alkaline batteries - LR03 - AAA 1,5V

#### NUMBER OF OPENINGS:

- Contactless versions: Up to 40,000 openings.
- Low battery power indication monitored through the SALTO Virtual Network (SVN).
- The last approx. 1,000 operations are signalled.

#### **ENVIRONMENTAL CONDITIONS:**

Not suitable for outdoor use.

## Main Features

- Fully integrated with the SALTO XS4 platform.
- Simple installation by changing handle set, using just two screws, whether installing on new or existing door standards.
- Easy to maintain: Battery change is all that's needed.
- For inside use: Attractive design is ideal for indoor use and easy to retrofit existing doors.
- User on card audit trailing capability via the SALTO Virtual Network (SVN).
- All communication between the carrier and the electronic lock is encrypted and secured.
- Low battery status information is obtained from carriers.
- Optical signalling through light ring. Dual colour green/ red to indicate access authorisation.
- The lock can always be opened from the inside (single action panic feature works in conjunction with the relevant mortise lock).
- Concealed fixing screws for greater security and improved aesthetics.
- Available in 2 different reader finishes: White and Black.
- Wide range of finishes, retrofits, handles and retrofit cover plates.
- Firmware upgrade through contactless PPD.
- Emergency opening via contactless portable programming device (PPD).

### Access Control Features

### **USERS & DOORS:**

- Maximum number of users per door: 4 million.
- Maximum number of doors per system: 65,000.
- Access levels: unlimited.

#### CALENDARS & TIME ZONES:

- Calendars in system: 256
- Time tables: 1024
- Time periods: 1024

#### **EVENTS:**

- Maximum events on lock audit: 2200.
- Non volatile memory (memory is not deleted, even if power fails).

#### MANAGEMENT SOFTWARE:

• SALTO ProAccess SPACE.

#### **ID TECHNOLOGIES:**

- Covering the mainstream MIFARE RFID technologies.
- Compatible with ISO 14443A, ISO 14443B and ISO 15693 (Vicinity).

## Lock Modes

STANDARD: Locked at all times.

#### OFFICE MODE: Free passage.

TIMED OFFICE: Automatic locking at end time.

#### AUTOMATIC OPENING:

8 pairs of "hands free" timed lock and unlocks per day with holidays.

TOGGLE: Present card to lock, present card to unlock.

#### TIMED TOGGLE:

Present card to lock, present card to unlock depending on schedules.